



Section 1: Identification

- Product Identity: Skilcraft® Dry Erase Chisel and Bullet Tip and Fine Point Markers in Black, Blue, Green, Red, Brown, Orange, Purple and Yellow.
- NSN Numbers: 7520-01-294-3791, 7520-01-510-5658, 7520-01-510-5659, 7520-01-510-5661, 7520-01-553-8142, 7520-01-510-5655, 7520-01-510-5662, 7520-01-510-5657, 7520-01-510-5660, 7520-01-186-3605, 7520-01-383-7950, 7520-01-557-4971, 7520-01-352-7321, 7520-01-365-6126, 7520-00-NIB-1749
- Manufacturer: Dallas Lighthouse for the Blind
4306 Capitol Avenue
Dallas, Texas 75204
- For information call: Director of Quality 214-821-2375
- In case of Emergency: Poison Control Center Contact: 800-222-1222
- Recommended use: Office and household use.
- Skilcraft® is a trademark recognized under NIB National Industries for the Blind and is a member of the Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D -4236 and is labeled with the AP Non-Toxic Seal. Products bearing the AP Approved Product Seal of the Art and Creative Materials Institute, Inc. are certified in a program of toxicological evaluation by a medical expert, subject to review by the Institute Toxicology Advisory Board, to contain no materials in sufficient quantities to be harmful to humans or to cause acute or chronic health problems.

Section 2: Hazard(s) Identification

- Dot Classification – Not Regulated (U.S.)
- TOG Classification – Not Regulated (Canada)
- ADR/RID Classification – Not Regulated (Europe)
- IMO/IMDG Classification – Not Regulated
- ICAO/IATA Classification – Not Regulated
- NFPA rating (scale 0-4)



Health: 0, Flammability: 3, Reactivity: 0



Flammable

Not hazardous under normal use conditions. Not for use on skin. Do not ingest. Contact with eyes may cause irritation. Vapors may cause drowsiness and dizziness.

Section 3: Composition/Information on Ingredients

Substances

- CAS# 64-17-5 Ethanol 50-100%
- CAS# 107-98-2 1-Methoxy-2-propanol 10-25%
- CAS# 67-63-0 propan-2-ol 2.5-10%

Mixtures

- Mixtures of the substances listed above with nonhazardous additions such as pigments, polymers, additives.

Product conforms to ASTM D -4236. Liquid ink in a polypropylene container, polyester fibrous reservoir, and polyester tip.

These Products are not considered to be a hazardous substance as defined under OSHA's Hazard Communication Standard 29 CFR 1910.1200 (b)(6)(ix).

Section 4: First-Aid Measures

- No special measures required.
- If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care.
- Generally, the product does not irritate the skin. If skin contact irritation occurs, wash with soap and water for 5 minutes.
- If inhaled, supply fresh air. If complaints persist, seek medical care.
- If swallowed, and symptoms persist, seek medical care.

Section 5: Fire-Fighting Measures

- Flash Point: 13°C(55°F)
- Auto Ignition: Product is not self-igniting.
- LEL: Not Established
- UEL: Not Established

A finished marker contains a substantially lower percentage by weight of each chemical and has the ink held within an absorbed material so it will be released from the marker only through the writing nib.

Section 6: Accidental Release Measures

- In case of spillage: wipe up with absorbent material

Section 7: Handling and Storage

- Do not shake marker.
- Keep cap on marker when not in use.
- Store markers horizontally when not in use
- Waste Disposal: IAW Federal, State and local laws.

Section 8: Exposure Controls/Personal Protection

- Respiratory Protections: None required under normal use conditions
- Ventilation: None required under normal use conditions
- PPE: (Gloves/glasses/clothing), none required under normal use conditions

Section 9: Physical and Chemical Properties

- Appearance: Colored liquid according to product specification.
- Upper/lower flammability or explosive limits; N/A
- Odor: Low
- Odor threshold: Not determined
- pH: : Not determined
- Melting point/freezing point: : Not determined
- Solubility: Partially miscible.
- Initial boiling point and boiling range: 78° C (172° F)
- Flash point: 13°C(55°F)
- Evaporation rate: Not determined
- Flammability (solid, gas): N/A
- Upper/lower flammability or explosive limits: Lower:1.7 Vol%, Upper:15.0 Vol%
- Vapor pressure @20°C (68°F): 59 hPa (44 mm Hg)
- Vapor density: Not determined
- Relative density: Not determined
- Partition coefficient: n-octanol/water: Not determined
- Auto-ignition temperature: 287°C (549°F)
- Decomposition temperature: Not determined
- Viscosity: 8 mPas

Section 10: Stability and Reactivity

Reactivity

- Chemical incompatibility: None

Chemical stability

- Chemical is stable under normal ambient temperature and conditions while in storage and being handled.

Other

- Hazard Decomposition or By-Products: None
- Polymerization will not occur

Section 11: Toxicological Information

- Chemicals listed as Carcinogens or Potential Carcinogens: None
- National Toxicology Program (NTP): None
- International Agency for Research on Cancer (IARC): None
- OSHA: None

Section 12: Ecological Information

- No data available at this time.

Section 13: Disposal Considerations

- IAW Federal, State and local laws.

Section 14: Transport Information

- No data at this time.

Section 15: Regulatory Information

- No data at this time.

Section 16: Other Information

The information contained in this Safety Data Sheet is based upon test data from Dokumental GmbH & KG Schreibfarben. To the best of our knowledge this information is correct. If further information is needed pertaining to this SDS, please contact Bernd Polzin of Documental at Business Ph., +49-621-5402322.

Revision Date	Description
07/11/2000	Initial Release
07/09/2010	-
04/07/2015	Changed format to conform with SDS requirements



Section 1: Identification

- Product Identity: Skilcraft® Dry Erase Cleaner
- NSN Numbers: 6580-00-NIB-0089
- Manufacturer: Dallas Lighthouse for the Blind
4306 Capitol Avenue
Dallas, Texas 75204
- For information call: Director of Quality 214-821-2375
- In case of Emergency: Poison Control Center Contact: 800-222-1222
- Recommended use: Office and household use.
- Skilcraft® is a trademark recognized under NIB National Industries for the Blind and is a member of the Art and Creative Materials Institute, Inc.

Section 2: Hazard(s) Identification

- Dot Classification – Not Regulated (U.S.)
- TOG Classification – Not Regulated (Canada)
- ADR/RID Classification – Not Regulated (Europe)
- IMO/IMDG Classification – Not Regulated
- ICAO/IATA Classification – Not Regulated
- NFPA rating (scale 0-4)



Health: 1, Flammability: 0, Reactivity: 0



Irritant

Not hazardous under normal use conditions. Not for use on skin. Do not ingest. May be harmful by ingestion or skin contact and may cause anemia. Contact with eyes may cause irritation. Vapors may cause dizziness. Use in a well ventilated area. Keep out of reach of children.

Section 3: Composition/Information on Ingredients

Substances

- CAS# 2807-30-9 Ethylene Glycol Monopropyl Ether 10-15%

Section 4: First-Aid Measures

- If eye contact occurs, rinse with water for 5-10 minutes. If irritation persists, seek medical care.
- If skin contact occurs, wash with soap and water for 5 minutes. If irritation persists, seek medical care.
- If inhaled, supply fresh air. If complaints persist, seek medical care.
- If swallowed, seek medical care. For further health information, contact the poison control center at 800-222-1222.

Section 5: Fire-Fighting Measures

- Flash Point: None
- Auto Ignition: Product is not self-igniting.
- LEL: Not Established
- UEL: Not Established

Section 6: Accidental Release Measures

- In case of spillage: wipe up with absorbent material

Section 7: Handling and Storage

- Keep cap on bottle when not in use.
- Store cool/dry location.
- Waste Disposal: IAW Federal, State and local laws.

Section 8: Exposure Controls/Personal Protection

- Respiratory Protections: None required under normal use conditions.
- Ventilation: Use in well ventilated area.
- PPE: (Gloves/glasses/clothing): None required under normal use conditions

Section 9: Physical and Chemical Properties

- Appearance: Clear liquid
- Upper/lower flammability or explosive limits; N/A
- Odor: Low
- Odor threshold: Not determined
- pH: : 11
- Melting point/freezing point: : Not determined
- Solubility: Complete.
- Initial boiling point and boiling range: Not determined
- Flash point: None
- Evaporation rate: (Butyl Acetate=1.0) Not determined
- Flammability (solid, gas): Not flammable
- Upper/lower flammability or explosive limits: Not determined
- Vapor pressure: Not determined
- Vapor density: Not determined
- Relative density: 8.5Lbs/Gal
- Partition coefficient: n-octanol/water: Not determined
- Auto-ignition temperature: N/A
- Decomposition temperature: Not determined
- Viscosity: ~1 mPas

Section 10: Stability and Reactivity

Reactivity

- Chemical incompatibility: None

Chemical stability

- Chemical is stable under normal ambient temperature and conditions while in storage and being handled.

Other

- Hazard Decomposition or By-Products: None
- Polymerization will not occur

Section 11: Toxicological Information

- Chemicals listed as Carcinogens or Potential Carcinogens: None
- National Toxicology Program (NTP): None
- International Agency for Research on Cancer (IARC): None
- OSHA: None

Section 12: Ecological Information

- No data available at this time.

Section 13: Disposal Considerations

- IAW Federal, State and local laws.

Section 14: Transport Information

- No data at this time.

Section 15: Regulatory Information

- No data at this time.

Section 16: Other Information

The information contained in this Safety Data Sheet is based upon test data from Wilpak Industries. To the best of our knowledge this information is correct. If further information is needed pertaining to this SDS, please contact Elliot Liebowitz of Wilpak Industries, Inc. at Business Ph., 201-997-7600.

Revision Date	Description
07/11/2000	Initial Release
08/01/2007	Revised
04/07/2015	Changed format to conform with SDS requirements